



FLOW BOX 10 - HIGH AIRFLOW DUST COLLECTOR



OEM ORIGINAL EQUIPMENT MANUFACTURERS



CHEMICAL-PHARMACEUTICAL



ELECTRONICS



- ✓ Complete steel construction
- ✓ High filtration efficiency
- ✓ High air flow value

- ✓ Conceived for the suction of fine dusts suspended in the air
- ✓ Articulated arm to suction in a restricted area
- ✓ Easily removable container for safe disposal of collected material



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	1,1
Electrical protection	IP	55
Max waterlift	mmH ₂ O	144 - 121
Max waterlift	mmH ₂ O	144 - 121
Max air flow	m ³ /h	1350 - 2100
Suction inlet	mm	150
Noise level (EN ISO 3744)	dB(A)	69



FILTER UNIT

Filter Type		Cartridge
Surface - Diameter	cm ² -mm	100.000
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M



COLLECTION UNIT

Discharge system		Roll-out container
Capacity	lt	5



VOLUME

Dimensions	cm	90x80x110h
Weight	kg	145



SUCTION UNIT

The suction unit is made of an electric fan which guarantees elevated air flow.



FILTER UNIT

The polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.



COLLECTION UNIT

The detachable steel collection tank has a quick release system for the rapid disposal of the sucked material.



OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST